

CalCarb® R1 **Ground Calcium Carbonate**

Discovering what's possible with calcium

PRODUCT DESCRIPTION

The Mississippi Lime CalCarb* Calcium Carbonate family of products is mined from the high purity formation in Ste. Genevieve, Missouri which consists of limestone with an average calcium carbonate content of 98.5%. CalCarb® R1 is a high purity, consistently sized 16 mesh calcium carbonate. Low iron, silica and magnesium levels make this product an excellent choice for glass-making applications as well as other chemical and industrial processes requiring a pure limestone.

TYPICAL CHEMICAL PROPERTIES			
CaCO ₃	98.5%		
MgCO ₃	0.6%		
SiO ₂	0.5%		
Al ₂ O ₃	0.1%		
Fe ₂ O ₃	0.06%		
Sulfur	0.03%		
H ₂ O	0.1%		

TYPICAL CHEMICAL PROPERTIES			
CaCO ₃	98.5%		
MgCO ₃	0.6%		
SiO ₂	0.5%		
Al_2O_3	0.1%		
Fe ₂ O ₃	0.06%		
Sulfur	0.03%		
H ₂ O	0.1%		
	·		

TYPICAL PHYSICAL				
PROPERTIES				
-16 Mesh (1190 μm)	99.9%			
-20 Mesh (840 μm)	esh (840 μm) 94%			
-30 Mesh (590 μm)	72%			
-100 Mesh (150 μm)	7%			
-120 Mesh (125 μm)	5%			
-140 Mesh (105 μm)	4%			
-200 Mesh (74 μm)	2%			
Particle Size Range	10μm-1100μm			
Apparent Dry Bulk Density - Loose	56 lbs/ft ³			
Apparent Dry Bulk Density - Packed	104 lbs/ft ³			

PARTICLE SIZE DISTRIBUTION					
	100				
(%)	80				
Vass	60				
tive /	40				
Cumulative Mass (%)	20				
ŭ	0				
	10	100 1000 ESD (μm)	10000		





Telephone: 800.437.5463 Contact: sales@mlc.com Web site: www.mlc.com

All information provided and recommendations made herein are intended to assist customers in determining whether our products are suitable for their applications. The values associated with all chemical and physical properties herein are typical values and are not intended to be used as product specifications or guarantees. ALL EXPRESS AND IMPLIED WARRANTIES ARE DISCLAIMED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. We request that customers inspect and test our products before use in order to make their own final decision regarding suitability. We do not guarantee results, freedom from patent infringement, or suitability of resultant products for any suggested application with respect to the use of any formula or material described herein.