MLC,

SAFETY DATA SHEET

1. Identification

Product identifier MLC™ MicroCal®O, PetroCal®O, and PolyCal®O Calcium Oxides

Other means of identification

CAS number 1305-78-8

Recommended use For commercial applications of calcium oxide powder in general chemical manufacturing, glass

and composites, plastics & polymers, coatings and adhesives, rubber, water treatment,

construction, and other unlisted industrial uses.

Recommended restrictions Not for use as direct food or pharma ingredients.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Mississippi Lime Company d/b/a MLC

Address: 16147 US Highway 61

Ste Genevieve, MO 63670

Phone Number: (800) 437-5463 **24 Hour Emergency** (866) 519-4752

Contact Number:

Access code: 336393

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1C

Serious eye damage/eye irritation Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause respiratory irritation. Harmful to aquatic

life.

Precautionary statement

Prevention Do not breathe dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated

area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to

the environment.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

MLC™ MicroCal®O, PetroCal®O, and PolyCal®O Calcium Oxides

944590 Version #: 08 Revision date: 29-October-2024 Issue date: 29-October-2024

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Calcium oxide (CaO)		1305-78-8	97 - 99
Impurities			
Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	≤ 1
Silicon Oxide		7631-86-9	≤ 1
Composition comments	Occupational Exposure Limits for impurities are listed in Section 8. All concentrations are in		

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, Inhalation

give artificial respiration. Call a poison center or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or Skin contact

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Do not rub eves. Immediately flush eves with plenty of water for at least 15 minutes. Remove Eve contact

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

center immediately.

percent by weight.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

blindness could result. May cause respiratory irritation.

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

General fire hazards

Use fire-extinguishing media appropriate for surrounding materials.

Do not use water as an extinguisher. The product reacts with water and will generate heat.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do it without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

The product is nonflammable and does not support combustion.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

MLC™ MicroCal®O, PetroCal®O, and PolyCal®O Calcium Oxides 944590 Version #: 08 Revision date: 29-October-2024 Issue date: 29-October-2024

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Prevent product from entering drains. Stop the flow of material, if this is without risk. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not get water inside containers. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Cover with DRY earth, DRY sand, or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Collect spill using a vacuum cleaner with a HEPA filter. Put material in suitable, covered, labeled containers.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Avoid contact with acids, water, and moisture. Protect from humidity. The substance is hygroscopic and will absorb water by contact with the moisture in the air. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

HE OCHA

U.S OSHA Impurities	Туре	Value	
Silicon Oxide (CAS 7631-86-9)	TWA	80 mg/m3	
US. OSHA Table Z-1 Permissible Ex	cposure Limits (PEL) for Air	Contaminants (29 CFR 1910.	1000)
Material	Туре	Value	
Silicon dioxide, crystalline silica-free (CAS 1305-78-8)	PEL	5 mg/m3	
Impurities	Туре	Value	Form
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
US. OSHA Table Z-3 Permissible Ex	cposure Limits (PEL) for Min	eral Dusts (29 CFR 1910.1000	
Impurities	Туре	Value	Form
Magnesium Oxide (CAS 1309-48-4)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silicon Oxide (CAS 7631-86-9)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		20 mppcf	
US. ACGIH Threshold Limit Values	(TLV)		
Material	Туре	Value	
Silicon dioxide, crystalline silica-free (CAS 1305-78-8)	TWA	2 mg/m3	
Impurities	Туре	Value	Form
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.

 $\mathsf{MLC^{TM}}$ MicroCal®O, PetroCal®O, and PolyCal®O Calcium Oxides

SDS US

944590 Version #: 08 Revision date: 29-October-2024 Issue date: 29-October-2024

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended				
Material	Туре	Value		
Calcium oxide (CaO) (CAS 1305-78-8)	IDLH	25 mg/m3		
Impurities	Туре	Value		
Magnesium Oxide (CAS 1309-48-4)	IDLH	750 mg/m3		
Silicon Oxide (CAS 7631-86-9)	IDLH	3000 mg/m3		
US. NIOSH: Pocket Guide to Cher	nical Hazards			
Material	Туре	Value		
Calcium oxide (CaO) (CAS 1305-78-8)	TWA	2 mg/m3		
Impurities	Туре	Value		
Silicon Oxide (CAS 7631-86-9)	TWA	6 mg/m3		

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection When working with powders or dusts, wear dust-proof chemical goggles and face shield unless full

facepiece respiratory protection is worn.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear NIOSH approved respirator appropriate for airborne exposure at the point of use. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Powder.

Color Light grey to White..

Odor Odorless.
Odor threshold Not available.

pH > 12.4 Saturated solution in water

Melting point/freezing point 4661.6 °F (2572 °C) Initial boiling point and boiling 5162 °F (2850 °C)

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Non flammable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available. Vapor pressure temp. 77 °F (25 °C)

> 77 °F (25 °C) Not available.

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Reacts

Partition coefficient Not available. (n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 3.34 g/cm3 **Explosive properties** Not explosive.

Molecular formulaCa-OMolecular weight56.08 g/molOxidizing propertiesNot oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable under the prescribed storage conditions.

Possibility of hazardous

reactions

Strong exothermic reaction with acids. Calcium oxide reacts exothermically with water to form calcium hydroxide. The heat generated by this reaction may ignite combustible materials.

Conditions to avoid Contact with incompatible materials. The substance is hygroscopic and will absorb water by

contact with the moisture in the air.

Incompatible materials Acids. Water, moisture. Humid air. Hydrogen fluoride. Phosphorus pentoxide. Boric oxide. Steam.

Many organic materials.

Hazardous decomposition

products

Contact with water: Calcium hydroxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause respiratory irritation. Prolonged inhalation may be harmful.

Skin contactCauses severe skin burns.Eye contactCauses serious eye damage.IngestionCauses digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Causes digestive tract burns. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Toxicological data

Impurities Species Test Results

Silicon Oxide (CAS 7631-86-9)

Acute Dermal

LD50 Rabbit > 5000 mg/kg, 24 Hours

MLC™ MicroCal®O, PetroCal®O, and PolyCal®O Calcium Oxides

944590 Version #: 08 Revision date: 29-October-2024 Issue date: 29-October-2024

Impurities Species Test Results

Inhalation

Dust

LC50 Rat > 0.14 mg/l, 4 Hours

Oral

LD50 Rat > 3300 mg/kg

Skin corrosion/irritation Causes severe skin burns.

Serious eye damage/eye Causes serious eye damage.

irritation

eye damage/eye Causes serious eye damago

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon Oxide (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Persistence and degradability The product solely consists of inorganic compounds which are not biodegradable.

Bioaccumulative potential No data available on bioaccumulation.

Mobility in soil No data available for this product.

Other adverse effects The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic

organisms.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local

regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1910 UN proper shipping name Calcium oxide Transport hazard class(es)

Class 8 **Subsidiary hazard** 8 Label(s) Packing group Ш

Environmental hazards

Marine pollutant No.

Special precautions for user Symbol A – Airfreight Regulated. This material is not subject to HMR when transported by

ground. Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB8, IP3, T1, TP33

154 Packaging exceptions 213 Packaging non bulk Packaging bulk 240

IATA

UN1910 **UN** number Calcium oxide **UN proper shipping name**

Transport hazard class(es) Class 8 Subsidiary hazard Ш Packing group **Environmental hazards** No.

ERG Code 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1910

UN proper shipping name **CALCIUM OXIDE**

Transport hazard class(es)

Class 8 **Subsidiary hazard** Packing group **Environmental hazards**

> Marine pollutant No.

EmS Not assigned.

Special precautions for user Not subject to the provisions of this Code but may be subject to provisions governing the

transport of dangerous goods by other modes. SP 960. Read safety instructions, SDS and

emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not applicable.

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

This substance is on the TSCA 8(b) inventory and is designated "active". **Toxic Substances Control Act (TSCA)**

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

MLC™ MicroCal®O, PetroCal®O, and PolyCal®O Calcium Oxides 944590 Version #: 08 Revision date: 29-October-2024 Issue date: 29-October-2024 Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Calcium oxide (CaO) (CAS 1305-78-8) Magnesium Oxide (CAS 1309-48-4) Silicon Oxide (CAS 7631-86-9)

US. New Jersey Worker and Community Right-to-Know Act

Calcium oxide (CaO) (CAS 1305-78-8) Magnesium Oxide (CAS 1309-48-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium oxide (CaO) (CAS 1305-78-8) Magnesium Oxide (CAS 1309-48-4) Silicon Oxide (CAS 7631-86-9)

US. Rhode Island RTK

Calcium oxide (CaO) (CAS 1305-78-8) Magnesium Oxide (CAS 1309-48-4) Silicon Oxide (CAS 7631-86-9)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(e) or region

Country(s) or region	inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Inventory name

Revision date 29-October-2024 29-October-2024

Version # 08

944590 Version #: 08 Revision date: 29-October-2024 Issue date: 29-October-2024

On inventory (vec/ne)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

HMIS® ratings

Health: 3 Flammability: 0 Physical hazard: 1

NFPA ratings



Disclaimer

Mississippi Lime Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

SDS US

944590 Version #: 08 Revision date: 29-October-2024 Issue date: 29-October-2024