MLC,

SAFETY DATA SHEET

1. Identification

Product identifier MLC™ Hydrated Lime Types N and S - Calera

Other means of identification

Product code Hydrated Lime Type N, Hydrated Lime Type S, Magnolia Type S, Calcium Hydroxide

Recommended use Industrial, Chemical, Construction, Environmental and Water Treatment Applications of Calcium

Hydroxide.

Recommended restrictionsNot approved for food, food contact or pharmaceutical applications.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Mississippi Lime Company d/b/a MLC

Address: 16147 US Highway 61

Ste Genevieve, MO 63670

Phone Number: 24 Hour Emergency Contact Number: (800) 437-5463 (866) 519-4752

Access code: 336393

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause

cancer. Harmful to aquatic life.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective

clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before

reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

MLC™ Hydrated Lime Types N and S - Calera

953437 Version #: 01 Revision date: - Issue date: 03-December-2024

SDS US

3. Composition/information on ingredients

Substances

Chemical name		CAS number	%
Calcium hydroxide		1305-62-0	93 - 100
Impurities			
Chemical name	Common name and synonyms	CAS number	%
Calcium Carbonate		471-34-1	< 5
Magnesium Oxide		1309-48-4	< 3
Silicon Dioxide		7631-86-9	< 2
Quartz (Crystalline Silica)		14808-60-7	< 0.75

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

tract, skin and eyes. Coughing. Skin irritation. May cause redness and pain.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove Eye contact

contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Symptoms may be delayed.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment

Do not use water jet as an extinguisher, as this will spread the fire.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. and precautions for firefighters

Use water spray to cool unopened containers.

Fire fighting equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards The product is nonflammable and does not support combustion.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not get this material in contact with eyes. Avoid breathing dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

Impurities	Туре	Value	
Silicon Dioxide (CAS 7631-86-9)	TWA	80 mg/m3	
US. OSHA Table Z-1 Permissible			
Components	Туре	Value	Form
Calcium hydroxide (CAS 1305-62-0)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Impurities	Туре	Value	Form
Quartz (Crystalline Silica) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
*			
US. OSHA Table Z-3 Permissible	Exposure Limits (PEL) for Mine	eral Dusts (29 CFR 1910.1000)	
US. OSHA Table Z-3 Permissible Impurities	Exposure Limits (PEL) for Mine Type	eral Dusts (29 CFR 1910.1000) Value	Form
Impurities Quartz (Crystalline Silica)	• • •	•	
	Туре	Value	Form
Impurities Quartz (Crystalline Silica)	Туре	Value 0.1 mg/m3	Form Respirable.
Impurities Quartz (Crystalline Silica) (CAS 14808-60-7) Silicon Dioxide (CAS	Type TWA	Value 0.1 mg/m3 2.4 mppcf	Form Respirable. Respirable.
Impurities Quartz (Crystalline Silica) (CAS 14808-60-7) Silicon Dioxide (CAS	Type TWA	Value 0.1 mg/m3 2.4 mppcf 5 mg/m3	Respirable. Respirable. Respirable fraction.
Impurities Quartz (Crystalline Silica) (CAS 14808-60-7) Silicon Dioxide (CAS 7631-86-9) Magnesium Oxide (CAS	Type TWA	Value 0.1 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3	Respirable. Respirable. Respirable fraction.
Impurities Quartz (Crystalline Silica) (CAS 14808-60-7) Silicon Dioxide (CAS 7631-86-9) Magnesium Oxide (CAS	Type TWA TWA	Value 0.1 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 20 mppcf	Respirable. Respirable. Respirable fraction. Total dust.
Impurities Quartz (Crystalline Silica) (CAS 14808-60-7) Silicon Dioxide (CAS	Type TWA TWA	Value 0.1 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 20 mppcf 5 mg/m3	Respirable. Respirable. Respirable fraction. Total dust. Respirable fraction.

Impurities	ssible Exposure Limits (PEL) for Min Type	Value	Form
Calcium Carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Components	Values (TLV) Type	Value	
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Impurities	Туре	Value	Form
Quartz (Crystalline Silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
NIOSH. Immediately Dange Impurities	rous to Life or Health (IDLH) Values, Type	as amended Value	
	<u> </u>		
Quartz (Crystalline Silica) (CAS 14808-60-7)	IDLH	50 mg/m3	
Silicon Dioxide (CAS 7631-86-9)	IDLH	3000 mg/m3	
Magnesium Oxide (CAS 1309-48-4)	IDLH	750 mg/m3	
US. NIOSH: Pocket Guide to			
Components	Туре	Value	
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Impurities	Туре	Value	Form
Quartz (Crystalline Silica) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Silicon Dioxide (CAS 7631-86-9)	TWA	6 mg/m3	
Calcium Carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
ogical limit values	No biological exposure limits noted f	or the ingredient(s).	
propriate engineering trols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Provide eyewash station and safety shower.		
vidual protection measures	, such as personal protective equipn	nent	
Eye/face protection	Use tight fitting goggles.		
Skin protection	Wear appropriate chemical resistant	gloves.	
Hand protection		•	

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece,

dust and mist filter.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Powder.
Color White.
Odor None.

Odor threshold Not available.

pH 12.4 In aqueous solution (77 °F (25 °C))

Melting point/freezing point 1076 °F (580 °C) Initial boiling point and boiling Not available.

range

Flash point Does not flash
Evaporation rate Not available.
Flammability (solid, gas) Non combustible.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure < 0.0000001 kPa (77 °F (25 °C))

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) 1.7 g/l at 20 °C

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density > 2.2 - < 2.3 g/cm3

Explosive properties Not explosive.

Molecular formula Ca-H2-O2

Molecular weight 74.1 g/mol

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity Reacts violently with strong acids.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials. Do not mix with other chemicals.

Incompatible materials Acids. Phosphorus. Maleic anhydride. Nitroethane. Nitroparaffins. Nitroparaffins. Nitroparaffins.

Hazardous decomposition

products

No hazardous decomposition products are known.

MLC™ Hydrated Lime Types N and S - Calera

953437 Version #: 01 Revision date: - Issue date: 03-December-2024

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye damage.

Ingestion May cause irritation of the gastrointestinal tract.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory

7340 mg/kg

tract, skin and eyes. Coughing. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

Calcium hydroxide (CAS 1305-62-0)

Acute Oral

LD50 Rat

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (Crystalline Silica) (CAS 14808-60-7) 1 Carcinogenic to humans.

Silicon Dioxide (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Quartz (Crystalline Silica) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (Crystalline Silica) (CAS 14808-60-7)

Cancer

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Test Results Components **Species**

Calcium hydroxide (CAS 1305-62-0)

Aquatic Acute

Fish LC50 Zambezi barbel (Clarias gariepinus) 33.9 mg/l, 96 hours

Persistence and degradability

The product contains inorganic compounds for which biodegradability is not applicable.

Bioaccumulative potential

No data available on bioaccumulation.

Mobility in soil

This product is slightly water soluble and may disperse in soil.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

> material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (Crystalline Silica) (CAS 14808-60-7)

lung effects

immune system effects

kidney effects

Toxic Substances Control Act (TSCA) This substance is on the TSCA 8(b) inventory and is designated "active".

953437 Version #: 01 Revision date: - Issue date: 03-December-2024

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Skin corrosion or irritation

categories Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Calcium Carbonate (CAS 471-34-1)

Calcium hydroxide (CAS 1305-62-0)

Magnesium Oxide (CAS 1309-48-4)

Quartz (Crystalline Silica) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9)

US. New Jersey Worker and Community Right-to-Know Act

Calcium Carbonate (CAS 471-34-1)

Calcium hydroxide (CAS 1305-62-0)

Magnesium Oxide (CAS 1309-48-4)

Quartz (Crystalline Silica) (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium Carbonate (CAS 471-34-1)

Calcium hydroxide (CAS 1305-62-0)

Magnesium Oxide (CAS 1309-48-4)

Quartz (Crystalline Silica) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9)

US. Rhode Island RTK

Calcium Carbonate (CAS 471-34-1)

Calcium hydroxide (CAS 1305-62-0)

Magnesium Oxide (CAS 1309-48-4)

Quartz (Crystalline Silica) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9)

California Proposition 65



WARNING: This product can expose you to SILICA, CRYSTALLINE QUARTZ, which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (Crystalline Silica) (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Europea List of Notified Chemical Substances (ELINCS)

MLC™ Hydrated Lime Types N and S - Calera

No

Country(s) or region Inventory name On inventory (yes/no)*

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

Yes

New ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-December-2024

Revision date - 01

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings



Disclaimer

Mississippi Lime Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.